

WBT Toploader



- * Capacities from 100g to 5100g
- * Readability from 0.001g to 0.1g
- * Stainless Weighing pan
- * Adjustable Leveling Feet with Level Bubble
- * AC (included) or 8 AA Bateriaes
- * Backlit LCD Display

Model	WBT-100	WBT-602	WBT-5001
Capacity (g)	100 g	600 g	5000 g
Readability (g)	0.001	0.01	0.1
Repeatability (g)	±0.003g	±0.02	±0.2
Weighing units	g, kg, oz, ct, lb, t, ozt, dwt, GN		
Zero range	To capacity by subtraction		
Stabilization time	3.5 seconds	2.5 seconds	
Optimum operating temp.	64°-77°F / 18°-25°C		
Power requirements	AC adapter (included) or 8-AA alkaline batteries		
Calibration	User calibration from keypad		
Display (in/mm)	LCD (0.75")		
Pan size L x W (in/cm)	3" dia	5" dia	7" x 6"
Dimensions L x W x H (in/cm)	9.5" (H) x 7.5" (W) x 10.5" (L)	3" (H) x 7.5" (W) x 10.5" (L)	
Draft Shield	6.5" x 6.5" x 6"	Optional	NA
Net Weight (lb/kg)	9 lb	6 lb	5.06 lb

Weighing Modes			
Model	WBT-600	WBT-5000	WBT-100
Gram (g)	600 x 0.01	5000 x 0.1	100 x 0.001
Kilogram (kg)	0.6 x 0.00001	5 x 0.0001	0.1 x 0.000001
Decimal Ounce (oz)	21.2 x 0.0001	176 x 0.001	3.52 x 0.00002
Carat (ct)	3000 x 0.05	25000 x 0.5	500 x 0.005
Decimal Pound (lb)	1.3 x 0.00001	11 x 0.0001	0.22 x 0.00001
Troy Ounce (ozt)	19.3 x 0.0001	160 x 0.001	3.2 x 0.00002
Pennyweight (dwt)	385.8 x 0.01	3215 x 0.1	64.3 x 0.001
Grain Unit (GN)	9259.4 x 0.1	77161.7 x 1	1543.2 x 0.01