March 2006

8200 Series

Hanging Scales - 13-inch Dial

The CHATILLON® 8200 Series hanging scale are crafted of chrome-plates steel with machines stainless steel pinions and a phosphor bronze rack combination for virtually frictionless performance. The 13-inch double dial reaches full capacity in three revolutions. Runners are indexed for each revolution. Brass air dashpots eliminate pointer oscillation.

The 8200 Series may be specified as a Class III "Legal for Trade" scale. Available in avoirdupois and metric models, the 8200 Series can be supplied with a bottom hook (nickel plated steel) or the popular AS circular pan. The AS Pan is constructed of stainless steel. The supporting ring and bow are of nickel plated steel. The removable 5-inch deep round pan has drain holes and is USDA approved for use in general food handling.

Features

- Avoirdupois and Metric Graduations
- Available as H44 Class III "Legal for Trade"
- ☐ Full Capacity in Three Pointer Revolutions
- Double 13-inch Dials (Glass Covered)
- Bottom Hook or AS Pan Attachments
- 1 Year Warranty

Specifications

Accuracy: (See Tables Below)

Maximum Overload: 120% of Rated Capacity

Tare Capacity: 10% Full Scale Capacity

Weight with Hook: 14 lbs (7 kg)
Weight with AS Pan: 18 lbs (9 kg)





Certificate of Conformance No. 88-060, Model 0028/A was issued under the national Type Evaluation Program of the National Conference on Weights and Measures, that the design conforms to NIST Handbook 44 Class III. The scale is "Legal for Trade" subject to on-site verification by the local Weights and Measures jurisdictions.

Accuracies - Class IIII

			Scale	Tolerance		
Model	Resolution	Range	Divisions	Division	Weight	%Accurate
8230DD-S	30 lb x 1 oz	0-3 lb	0-50	<u>+</u> 1/2 d	<u>+</u> 0.5 oz	<u>+</u> 0.10%
	4-5-5-5	4-12 lb	51-200	<u>±</u> 1 d	<u>+</u> 1 oz	±0.21%
		13-20 lb	201-400	<u>+</u> 1-1/2 d	±1.5 oz	<u>+</u> 0.31%
		26-30 lb	401 +	<u>+</u> 2-1/2 d	+2.5 oz	<u>+</u> 0.52%
8260DD-S	60 lb x 2 oz	0-3 lb	0-50	<u>+</u> 1/2 d	+0.5 oz	<u>+</u> 0.05%
THE REAL PROPERTY.		4-12 lb	51-200	<u>+</u> 1 d	<u>+</u> 1 oz	<u>+</u> 0.10%
		13-20 lb	201-400	<u>+</u> 1-1/2 d	<u>+</u> 1.5 oz	<u>+</u> 0.16%
		26-30 lb	401 +	<u>+</u> 2-1/2 d	+2.5 oz	<u>+</u> 0.26%
K8215DD-S	15 kg x 50 g	0-1 kg	0-50	<u>+</u> 1/2 d	<u>+</u> 10 g	±0.07%
	2000	2-4 kg	51-200	<u>+</u> 1 d	<u>+</u> 20 g	<u>+</u> 0.13%
		5-8 kg	201-400	<u>+</u> 1-1/2 d	<u>+</u> 30 g	±0.20%
		9-15 kg	400 +	<u>+</u> 2-1/2 d	<u>+</u> 50 g	±0.33%
K8230DD-S	30 kg x 50 g	0-2 kg	0-50	<u>+</u> 1/2 d	<u>+</u> 25 g	<u>+</u> 0.08%
	THE PROPERTY.	3-10 kg	51-200	<u>+</u> 1 d	+50 g	+0.17%
		11-20 kg	201-400	<u>+</u> 1-1/2 d	<u>+</u> 75 g	+0.25%
		21-30 kg	400 +	+2-1/2 d	+120 g	+0.42%

Accuracies - Class III "Legal for Trade"

	Resolution		Scale Divisions	Tolerance			
Model		Range		Division	Weight	%Accurate	ırate
8230DD-T	30 lb x 1/2 oz	0-15 lb	0-500	<u>+</u> 1/2 d	±0.25 oz	±0.05%	
		16-30 lb	501-2000	±1 d	±0.5 oz	±0.05%	
8260DD -T	60 lb x 1 oz	0-31 lb	0-500	<u>+</u> 1/2 d	±0.5 oz	±0.05%	
	10000	32-60 lb	501-2000	<u>+</u> 1 d	<u>+</u> 1 oz	<u>+</u> 0.10%	
K8215DD-T	15 kg x 20 g	0-10 kg	0-500	+1/2 d	±10 g	±0.07%	
		11-15 kg	501-2000	<u>+</u> 1 d	<u>+</u> 20 g	±0.13%	

These accuracies and tolerances are based on Handbook 44 Guidelines.



Dimensions Accessories Part No. **Description** 5854 Bottom Hook SPK-SCALE-AS AS Pan Assembly (4 lbs) AS Pan Only 7436-1 Bow, for AS Pan 16097 16098 Ring, for AS Pan 19 18 22' 15-1/2 16 13" 5 15 Chatillon 22" 14 13 12 11 26-5/16" 10 8 410 15-1/4" 12-1/4" 15-1/4" 4-5/16" 12" 5"

Ordering

H44 Class III "Legal for Trade"

Old Model	New Model	Capacity	Dial	Attachment
0628HDD	8230DD-T-H	30 lb x 1/2 oz	Double	Bottom Hook
5628ASDD	8230DD-T-AS	30 lb x 1/2 oz	Double	AS Pan
0728HDD	8260DD-T-H	60 lb x 1 oz	Double	Bottom Hook
5728ASDD	8260DD-T-AS	60 lb x 1 oz	Double	AS Pan
K0628HDD	K8215DD-T-H	15 kg x 20 g	Double	Bottom Hook
K5628ASDD	K8215DD-T-AS	15 kg x 20 g	Double	AS Pan

Certificate of Conformance No. 88-060, Model 0028/A was issued under the national Type Evaluation Program of the National Conference on Weights and Measures, that the design conforms to NIST Handbook 44 Class III. The scale is "Legal for Trade" subject to on-site verification by the local Weights and Measures jurisdictions.

H44 Class IIII "Legal for Trade"

Old Model	New Model	Capacity	Dial	Attachment	
8230HDD	8230DD-S-H	30 lb x 1 oz	Double	Bottom Hook	
8230ASDD	8230DD-S-AS	30 lb x 1 oz	Double	AS Pan	
8260HDD	8260DD-S-H	60 lb x 1 oz	Double	Bottom Hook	
8260ASDD	8260DD-S-AS	60 lb x 1 oz	Double	AS Pan	
8215KGHDD	K8215DD-S-H	15 kg x 20 g	Double	Bottom Hook	
8215KGASDD	K8215DD-S-AS	15 kg x 20 g	Double	AS Pan	
8230KGHDD	K8230DD-S-H	30 kg x 50 g	Double	Bottom Hook	
8230KGHASDI	DK8230DD-S-AS	30 kg x 50 g	Double	AS Pan	

AMETEK

US GAUGE DIVISION

 $For the \ authorized \ Chatillon \ Distributor \ or \ Manufacturer's \ Representative \ near \ you, \ go \ to \ www.chatillon.com$

Americas

AMETEK US Gauge Division

8600 Somerset Drive

Largo, Florida 33773

United States of America

Tel +1-727-536-7831

Tel +1-800-527-9999

Fax +1-727-539-6882

Email chalillon.fl-lar@ametek.com

United Kingdom Lloyd Instruments Ltd. 12 Barnes Wallis Road Segensworth East Fareham Hants, PO15 5TT United Kingdom Tel +44 (0) 1489 486 399 Fax +44 (0) 1489 885 118 France
AMETEK S.A.S.
Rond Point de l'Epine des Champs
Buro Plus - Bat. D
78990 Elancourt
France
Tel +33 (0)1 30 68 89 40
Fax +33 (0)1 30 68 89 49
Email general@lloyd-instruments.com

Germany
AMETEK GmbH
Rudolf-Diesel-Strasse 16
D-40670 Meerbusch
Germany
Tel +49 (0)2159 9136-70
Fax +49 (0)2159 9136-39
Email info@ametek.de

Singapore
AMETEK Singapore Pvt. Ltd.
10 Ang Mo Kio Street 65
#05-12 Techpoint
Singapore 569059
Tel +65-484-2388
Fax +65-481-6588
Email aspi@ametek.com.sq

Visit Us on the Worldwide Web at: www.chatillon.com

© 2006 by AMETEK, Inc.

Information within this document is subject to change without notice.